

Sonic technical specification



.mdd

.mdd has a leading position among manufacturers of office furniture with many awards that prove quality and continuously increase demand for it's products.

The realities of today`s market require constant quality improvement at all levels of modern organization. This applies in particular to customer service, marketing, quality of products and also to quality of processes within the company. Partnership relations among employees and with business partners form a base of economic growth and success of the company.

Constant investments in innovative machinery park, optimization of managment systems and an expansion of production halls allow to minimize the lead times for the product of the highest quality.

More than twenty years of experience in office furniture industry come with reference from a long list of companies and institutions to show their appreciation for an efficient and comprehensive service.

.mdd is hgly aware of the environment.

Being located in the forest region with lake by itis side, .mdd takes the nature seriously and invests constantly in a modern and energy-efficient solutions to preserve the local life. Company puts emphasis on waste segregation and recycling. .mdd has been awarded for the exceptional care and involvement in waste disposal. All materials used are environmentally friendly and enjoy a high 95 % rate of being recycled.



General informations:

Warranty:

.mdd products - **5 years**.
Electrical components and
fabric - **2 years**.

Certificate - MFC:



Certificate - fabric:



Assembly:

product delivered in separate
elements

Packing:

cardboard, packing film


Compliant with standards:

PN-EN ISO 354:2005

Boards density:

12 mm - 690 - 750 kg/m³
18 mm - 650 - 690 kg/m³
28 mm - 610 - 630 kg/m³
36 mm - 610 - 630 kg/m³

Material composition *:



* according to the EPD document

Recyclability **

Recycling: 0% - Downcycling: 100%

Recycled content


18%

Co2 carbon footprint

7,7 kg

** average values for a representative of the group;
values may vary for other products


Desktop screens - for single and bench screens



1. **Sonic screens** - upholstered, accoustic class A, pinable
2. **Zip fastener**
3. **Frame** - glued solid wood structure
4. **Filling** - acoustic nonwoven with high sound absorption and dispersion properties
5. **Steel bracket** - situated in the frame with a machine screw thread to stabilize bracket fixing (concerns desk screens)


Screen fixings

1. **Ogi, Ergonomic Master** - panel fixing for single desks (OPTION WITH EXTRA CHARGE); suitable for mounting to 16-30mm thick worktops
2. **Ogi** - brackets for benches included; powder-coated steel; suitable for mounting to 16-30mm thick worktops



Ogi Drive handle - dimensions (mm)

1. **Ogi Drive screen bracket** - an option with extra charge; mountable to the frame; powder-coated metal, 60x60mm profile




Caution - Ogi Drive screen bracket does not allow for pairing with screens equipped with accessories rail.

Sonic	Date of preparation 12.05.2023	The data contained in this document is valid in the day of its preparation. Change of the product, as long as it does not affect the basic features of it, does not require consistent updates of the document.	page 3/20 technical specification
-------	-----------------------------------	---	--------------------------------------

Screen brackets for sliding top desks


- 1. Single desk bracket - mountable to the metal beam
- 2. Brackets for benches - mountable to the metal beam



Attention - the screen should be mounted before the worktop assembly.


Desktop screens - for single desks

- 1. Fabric - accoustic class A, pinable
- 2. Fixing element - powder coated metal
- 3. Zip fastener




Partition screens - for bench desks

- 1. Sonic screens - acoustic class A, pinnable, zip colour - graphite
- 2. Side screen fixings for Ogi desks - foot 2 pcs



Side screens - for single and bench desks


- 1. Sonic screens - accoustic class A, zip fastener, pinable
- 2. Fixing for side panels - powder coated metal, colour: M009 - aluminium semi-matt



Accessories for function rail

- 1. Accessories rail - max load: 3.5 kg per point, 7 kg per side
- 2. Monitor holder - powder coated steel, colour: M009 - aluminium semi-matt
- 3. Pencil case - powder coated steel
- 4. Shelf - A4 size, powder coated steel
- 5. Organizer - powder coated metal

www.mdd.eu



ATTENTION: Only accessories from .mdd offer can be mounted


Desktop screens - for single and bench screens *




ZUS01
990 / 40 / 350
4.1 kg




ZUS12
1190 / 40 / 350
5.4 kg




ZUS14
1390 / 40 / 350
6.1 kg



ZUS16
1590 / 40 / 350
6.8 kg



ZUS18
1790 / 40 / 350
7.2 kg




ZUS20
1990 / 40 / 350
8.2 kg




ZUS05
990 / 40 / 500
4.8 kg




ZUS52
1190 / 40 / 500
6 kg




ZUS54
1390 / 40 / 500
7.1 kg



ZUS56
1590 / 40 / 500
7.8 kg



ZUS58
1790 / 40 / 500
8.4 kg



ZUS59
1990 / 40 / 500
8.3 kg

* dimensions expressed in millimeters: width x depth x height


Desktop screens - for sliding top bench desks *




ZUS01S
990 / 40 / 350
6.1 kg




ZUS12S
1190 / 40 / 350
7.4 kg




ZUS14S
1390 / 40 / 350
8.1 kg



ZUS16S
1590 / 40 / 350
8.8 kg




ZUS18S
1790 / 40 / 350
9.2 kg




ZUS20S
1990 / 40 / 350
10.2 kg




ZUS05S
990 / 40 / 500
6.8 kg




ZUS52S
1190 / 40 / 500
8 kg




ZUS54S
1390 / 40 / 500
9.1 kg



ZUS56S
1590 / 40 / 500
9.8 kg




ZUS58S
1790 / 40 / 500
10.4 kg




ZUS59S
1990 / 40 / 500
10.3 kg

* dimensions expressed in millimeters: width x depth x height


Desktop screens - for single desks *




ZPS610
990 / 40 / 650
8.1 kg




ZPS612
1190 / 40 / 650
6.3 kg




ZPS614
1390 / 40 / 650
7.3 kg




ZPS616
1590 / 40 / 650
8 kg




ZPS618
1790 / 40 / 650
7.9 kg




ZPS620
1990 / 40 / 650
10 kg




ZPS810
990 / 40 / 800
9.1 kg




ZPS812
1190 / 40 / 800
7.6 kg




ZPS814
1390 / 40 / 800
8.3 kg



ZPS816
1590 / 40 / 800
9.1 kg




ZPS818
1790 / 40 / 800
9.6 kg




ZPS820
1990 / 40 / 800
10.5 kg

* dimensions expressed in millimeters: width x depth x height


Desktop screens - for single desks Ogi Drive, Ogi T *




ZPS632
1190 / 40 / 650
5 kg




ZPS634
1390 / 40 / 650
6 kg




ZPS636
1590 / 40 / 650
7 kg




ZPS638
1790 / 40 / 650
8.2 kg




ZPS640
1990 / 40 / 650
10 kg




ZPS832
1190 / 40 / 800
16 kg




ZPS834
1390 / 40 / 800
8 kg





ZPS836
1590 / 40 / 800
8.5 kg



ZPS838
1790 / 40 / 800
9.5 kg




ZPS840
1990 / 40 / 800
10.5 kg




www.mdd.eu

* dimensions expressed in millimeters: width x depth x height


Desktop screens - for sliding top single desks *




ZPS610S
990 / 40 / 650
7 kg




ZPS612S
1190 / 40 / 650
7.1 kg




ZPS614S
1390 / 40 / 650
7 kg




ZPS616S
1590 / 40 / 650
8 kg




ZPS618S
1790 / 40 / 650
9.2 kg




ZPS620S
1990 / 40 / 650
11 kg




ZPS810S
990 / 40 / 800
8 kg




ZPS812S
1190 / 40 / 800
7 kg




ZPS814S
1390 / 40 / 800
9 kg



ZPS816S
1590 / 40 / 800
9.5 kg




ZPS818S
1790 / 40 / 800
10.5 kg




ZPS820S
1990 / 40 / 800
11.5 kg

* dimensions expressed in millimeters: width x depth x height


Desktop screens - for Ogi Drive bench desks *




ZD812
1190 / 40 / 800
6.1 kg




ZD814
1390 / 40 / 800
8.6 kg



ZD816
1590 / 40 / 800
7.9 kg




ZD818
1790 / 40 / 800
8.9 kg




ZD820
1990 / 40 / 800
9.3 kg

Partition screens - for Ogi bench desks *



ZYS78
1600 / 40 / 350
12 kg



ZYS79
1600 / 40 / 500
6.6 kg



ZOS58
577 / 40 / 350
3.5 kg



ZOS68
677 / 40 / 350
2.7 kg



ZOS78
780 / 40 / 350
3.2 kg



ZOS10
577 / 40 / 500
3.1 kg

* dimensions expressed in millimeters: width x depth x height

Partition screens – for Ogi bench desks *




ZOS40
677 / 40 / 500
3.4 kg




ZOS79
780 / 40 / 500
3.7 kg


Side screens – for single desks *



ZUS80
600 / 40 / 650
4.5 kg




ZUS90
700 / 40 / 650
4.6 kg




ZUS30
800 / 40 / 650
5.2 kg



ZUS60
600 / 40 / 800
7.7 kg




ZUS70
700 / 40 / 800
5.4 kg




ZUS50
800 / 40 / 800
6.1 kg

* dimensions expressed in millimeters: width x depth x height


Side screens - for bench desks *




ZUS11
1200 / 40 / 650
5.4 kg




ZUS41
1400 / 40 / 650
7.1 kg




ZUS31
1600 / 40 / 650
7.8 kg



ZUS61
1200 / 40 / 800
7.5 kg




ZUS71
1400 / 40 / 800
12 kg



ZUS51
1600 / 40 / 800
9.1 kg


Function rail accessories *



D1
300 / 130 / 130
1.9 kg



D5
164 / 83 / 146
0.2 kg




D6
327 / 35 / 210
0.95 kg




D7
93 / 250 / 180
0.6 kg

* dimensions expressed in millimeters: width x depth x height


Protective panel *




PUX12
1190 / 4 / 350
4.9 kg




PUX14
1390 / 4 / 350
5 kg



PUX16
1590 / 34 / 350
7 kg



PUX18
1790 / 4 / 350
6.5 kg




PUX20
1990 / 4 / 350
7 kg



PUX80
577 / 4 / 350
2.15 kg




PUX90
677 / 4 / 350
3.2 kg



PUX30
777 / 4 / 350
3.1 kg

* dimensions expressed in millimeters: width x depth x height

Fabric Nemo



Technical data:

Material	polyester 100%
Fabric weight	366g/m2
Abrasion resistance rubs	PN_EN ISO 12947 - 2:2 100,000
Pilling resistance	scale 1-8, max. 8, PN-EN ISO 105 - B02 (3-4)
Colour fastness to light	scale 1-5, max. 5, PN-EN 1021 - 2,
Colour fastness to rubbing	PN-EN 1021 - 1
	skscale 1-5, max. 5, EN ISO 105x12 (wet/dry) 4-5

Fabric Runner - second price group



Technical data:

Material	80% polyester, 20% post-consumer recycled polyester
Fabric weight	510 g/lm (16.45 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2 70,000 Martindale cycles
Pilling resistance	scale 1-5, max 5, EN ISO 12945-2 (4-5)
Colour fastness to light	scale 1-8, max 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max 5, EN ISO 105x12 (wet/dry) 4-5
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021-2 Match, CA TB 117-2013, BS EN 1021-1 (cigarette) Class Uno UNI 9175 Class 2, EMME

Fabric Medley - second price group



Technical data:

Material	polyester 100%
Fabric weight	510 g/lm (16.45 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2, 75,000 cykli Martindale
Pilling resistance	scale 1-5, max. 5, EN ISO 12945-2 (4)
Colour fastness to light	scale 1-8, max. 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max. 5, EN ISO 105x12 (wet/dry (4-5/4-5)
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021-1 (cigarette) BS 476 Part 7, Class 2 Class Uno UNI 9174 - UNI 8457 CA TB 117-2013 ASTM E 84 Class I

Fabric Atlantic * - second price group



Technical data:

Material	polyester 100%
Fabric weight	530 g/lm (17.09 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2, 110,000 Martindale cycles
Pilling resistance	scale 1-5, max. 5, EN ISO 12945-2 (4-5)
Colour fastness to light	scale 1-8, max. 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max. 5, EN ISO 105x12 (wet/dry)
Flammability	CA TB 117-2013 ASTM E 84 Class I BS EN 1021-2 (match) BS EN 1021-1 (cigarette)

Fabric Vita - second price group



Technical data:

Material	Surface: 98,5% PVC, 1,5% PU Substrate: 50% polyester, 50% Cotton
Fabric weight	850g/m2 ± 10% (1190G/lin. m ± 10%)
Abrasion resistance rubs	BS EN ISO 5470-2, 100,000 Martindale cycles
Colour fastness to light	6 (ISO 105 - B02)
Colour fastness to rubbing	wet: 4, dry: 4 (ISO 105 - X12)
Flammability	BS EN 1021 - (cigarette) BS EN 1021 - 2 (match) BS 5852 - (Ignition Source 5) BS 7176 - (Medium Hazard)
Flexes	BS EN ISO 7854 - Method B, 400.000 Flexing cycles
Anti-microbial / Anti-fungal	AATCC 147

Fabric Mica - second price group




Technical data:

Material	post-consumer recycled polyester 97%, polyester 3%
Fabric weight	305 g/lm
Abrasion resistance rubs	60,000 rubs martindale (EN ISO 12947-2)
Pilling resistance	scale 1-5, max. 5 - EN ISO 12945-2, 4-5
Light fastness	scale 1-8, max. 8 - EN ISO 105-B02, 5-8
Rubbing fastness	dry: 4-5, wet: 4-5, scale 1-5, max. 5 - EN ISO 105x12
Flammability	CA TB 117-2013 ASTM E 84 Class I BS EN 1021-1 Cigarette BS EN 1021-2 Match BS 476 Part 7 class I

* There is a possibility of ordering the product in full colour spectrum of Atlantic range, as per Gabriel's pattern book, within 8 weeks

Sonic	Date of preparation 12.05.2023	The data contained in this document is valid in the day of its preparation. Change of the product, as long as it does not affect the basic features of it, does not require consistent updates of the document.	page 16/20
			colours


Fabric Go Check - second price group

			
G-66136 Blue	G-66135 Light blue	G-60080 Dark grey	G-66138 Navy blue
			
G-60084 Dark graphite	G-68149 Dark green	G-68152 Green	G-60079 Grey
			
G-64183 Marsala	G-63079 Orange	G-64171 Red	G-64172 Burgundy
			
G-61144 Brown	G-61145 Dark brown		

Technical data:

Material	100% Trevira CS
Fabric weight	435g/lm
Abrasion resistance rubs	80,000 rubs martindale (EN ISO 12947-2)
Pilling resistance	scale 1-5, max. 5 - EN ISO 12945-2, 5
Light fastness	scale 1-8, max. 8 - EN ISO 105-B02, 5-8
Rubbing fastness	dry: 4-5, wet: 4-5, scale 1-5, max. 5 - EN ISO 105x12
Flammability	BS EN 1021 1&2 Cigarette and Match BS EN 1021-1 Cigarette BS 5852 Crib 5 BS 7176 Medium hazard DIN 4102 - B1 NFP 92-503/504/505 M1 ÖNORM A3800-B1-B3825-Q1 UK Class Uno UNI 9175 Class 1 I EMME FAR/JAR 25.853 (a) (i) (ii) CA TB 117-2013 DIN EN 13501-1 B-s1,d0 AM 18 - NF D 60-013-(only for fabric)

Fabric Charles * - second price group

			
C-01 Black	C-05 Grey	C-06 Beige	C-14 Brown
			
C-18 Rusty	C-21 Red	C-30 Pink	C-31 Marsala
			
C-32 Dark blue	C-35 Blue	C-41 Yellow	C-44 Olive
			
C-45 Green			

Technical data:

Material	100% polyester
Fabric weight	433g/m2
Abrasion resistance rubs	90,000 Martindale cycles (EN ISO 12947-2)
Pilling resistance	EN ISO 12945-2, 5
Light fastness	EN ISO 105-B02, 5
Rubbing fastness	dry: 4-5, wet: 4-5, EN ISO 105x12
Flammability	EN 1021, 1

* There is a possibility of ordering the product in full colour spectrum of Charles range, as per Dekoma pattern book, within the standard delivery time.

Fabric Synergy – third price group



Technical data:	
Composition	95% Virgin Wool, 5% Polyamide
Fabric weight	400g/m ² (560g/lm)
Abrasion resistance rubs	100.000 Martindale cycles
Colour fastness to light	ISO 105 – B02
Colour fastness to rubbing	EN ISO 105x12 (dry/wet)
Flammability	EN 1021 – 1&2 (cigarette & match) BS 7176 Low Hazard NF D 60-013 ÖNORM B 3825 & A 3800-1 (58 kg/m ³ CMHR Foam) UNI 9175 Classe 1 IM EN 13501-1 Adhered Class D, s1, d0 IMO FTP Code (Part 8) The Furniture and Furnishing (Fire) (Safety) Regulations 1988 (Domestic Cigarette and Match) BS 5852 Ignition Source 5 when FR treated BS 7176 Medium Hazard when FR treated EN 13501-1 Adhered Class B, s1, d0 when FR treated EN 13501-1 Un-adhered Class D, s2, d0 when FR treated BS 5867-2: Type B Curtains & Drapes when FR treated

Fabric Silvertex – third price group

Technical data:	
Material	Topcoat: 100% Vinyl Backing: 100% Polyester Hi-Loft™
Fabric weight	685 gr/m ²
Abrasion resistance	>300,000 cycles Martindale
UV-resistance	>= 7 (1000 hours, blue wool scale)
Cold Crack resistance	-23°C
Flame retardancy	NF P 92-503 / M2 EN 1021, Part 1&2 DIN 4102 B2 ÖNORM B 3825, Gruppe I – Schwerbrennbares Verhalten ÖNORM A 3800, Teil I, Qualmbildungsklasse QI – schwachqualmend IMO Res. MSC.307 (88) (2010 FTP Code) Annex I Part 8 (MED) Marine Equipment Directive in its current valid version UNI 9175 (1987) / UNI 9175/FAI (1994) Classe I.IM (uno I EMME) UNE 23.727-90 IR /M2 EN 71-2: 2006+AI: 2007 Safety of Toys – Part 2: Flammability ECE R 118 (replaces Directive 95/28/EC) FMVSS 302 FAR 25/853
Antimicrobial	Antifungal Protection, Antibacterial Protection, Antimycotic Protection

There is a possibility of ordering the product in full colour spectrum of Silvertex range, as per Spradling's pattern book, within 15 working days.

Fabric Tessa - third price group



Technical data:

Material	95% polyester, 5% acrylic
Fabric weight	500g/m ²
Abrasion resistance rubs	75,000 Martindale cycles (EN ISO 12497-2)
Pilling resistance	EN ISO 12945-2, 4-5
Light fastness	EN ISO 105-B02, 4
Rubbing fastness	dry: 4-5, wet: 4-5, EN ISO 105x12


Fabric Oceanic - third price group



Technical data:

Material	100% post-consumer recycled polyester
Fabric weight	497g/m ²
Abrasion resistance rubs	100,000 Martindale cycles (EN ISO 12947-2)
Pilling resistance	EN ISO 12945-2, 5
Light fastness	EN ISO 105-B02, 5
Rubbing fastness	dry: 4, wet: 4, EN ISO 105x12
Flammability	EN 1021, - 1&2 (Cigarette and Match) BS 7176 Low Hazard BS 5852 Ignition Source BS 7176 Medium Hazard

Fabric Quest - third price group



Technical data:

Material	100% post-consumer recycled polyester
Fabric weight	330g/m ²
Abrasion resistance rubs	100,000 Martindale cycles (EN ISO 12947-2)
Light fastness	EN ISO 105-B02, 4-6
Rubbing fastness	dry: 4, wet: 4, EN ISO 105x12
Flammability	EN 1021, - 1&2 (Cigarette and Match) BS 7176 Low Hazard UNI 9175 Classe 1 IM BS 476 Part 7 Class 1Y (Adhered) EN 13501-1 Adhered Class B, s1, d0 EN 13501-1 Un-adhered Class B, s1, d0 BS 5852 Ignition Source 5 with EnviroFlam5 BS 7176 Medium Hazard with EnviroFlam5 IMO FTP Code (Part 8) with EnviroFlam5

Fabric Grain - third price group



Technical data:

Material	92% post-consumer recycled polyester 8% polyester
Fabric weight	615g/m ²
Abrasion resistance rubs	100,000 Martindale cycles (EN ISO 12947-2)
Pilling resistance	EN ISO 12945-2, 5
Light fastness	EN ISO 105-B02, 5-7
Rubbing fastness	dry: 4-5, wet: 4-5, EN ISO 105x12
Flammability	BS EN 1021 1&2 Cigarette and Match BS EN 1021-1 Cigarette CA TB 117-2013

Fabric Atlas – fourth price group



AS-531
Orange



AS-501 Pink



AS-651 Red



AS-681 Burgundy



AS-391 Brown



AS-781 Navy blue



AS-161 Dark
grey



AS-111 Light grey



AS-971 Light
green



AS-981 Dark
green

Technical data:

Material	90% new wool, 10% nylon
Fabric weight	286g/m2, 400g/lm
Abrasion resistance rubs	100,000 cykli Martindale, EN ISO 12947
Colour fastness to light	ISO 105 B02: 6-7
Colour fastness to rubbing	ISO 105-X12:2001, (wet/dry) 4-5/4-5
Flammability	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5 5852 Crib 5, BS 5852 ignition source 3, BS 5852 Part 1, NF D 60 013, UNI 9175 1IM, US Cal. Bull. 117-2013

Bracket



M009 Aluminum
semi-matt RAL9006



M015 White
semi-matt RAL9010



M154 Anthracite
semi-matt RAL7043



M115 Black
semi-matt RAL9005

Accessories



M009 Aluminum
semi-matt RAL9006